

R550 Extreme Durable Resin

RIBBON PROPERTIES

Ink Color	Black
Base Film Thickness	4.5 ± 0.4 μ
Ink Thickness	2.0 ± 0.5 μ
Total Thickness	6.5 ± 0.9 μ
Transfer Temperature	357°F / 181°C

PRODUCT FEATURES

- FDA Indirect Food Contact
- REACH Compliant
- RoHS Compliant
- Halogen-free

RECOMMENDED SUBSTRATES

SYNTHETICS	SPECIALTY MATERIALS
Polypropylene	Polyimide
Polyethylene	PVC Shrink Wrap
Polystyrene	
Vinyl (Topcoat)	
Polyesters (Gloss)	
Polyesters (Matte)	

RECOMMENDED APPLICATIONS

AUTOMOTIVE



CHEMICALS



ELECTRONICS



FOOD & BEVERAGE



INVENTORY & LOGISTICS



OUTDOOR



PHARMACEUTICAL



RETAIL



UL / cUL LABELING REFERENCES

Avery Dennison:	PGJI8.MH17205, PGJI8.MH20580, PGJI8.MH26285
FLEXcon:	PGJI2.MH16635
Mactac:	PGJI2.MH26726

The information on this datasheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

DNP Imagingcomm America Corporation

1001 Technology Drive | Mount Pleasant, PA 15666
 Phone: 1.888.569.7222 | Fax: 1.800.676.7669
 Email: info@dnp.imagingcomm.com | Web: am.dnpribbons.com

