

M260 Ultra Durable Wax/Resin

RIBBON PROPERTIES

Ink Color	Black
Base Film Thickness	4.0 ± 0.4 µ
Ink Thickness	3.5 ± 0.5 µ
Total Thickness	7.5 ± 0.9 µ
Transfer Temperature	174°F / 79°C

PRODUCT FEATURES

- FDA Indirect Food Contact
- REACH Compliant
- RoHS Compliant
- Halogen-free

RECOMMENDED SUBSTRATES

TAG / PAPER	SYNTHETICS	SPECIALTY MATERIALS
Uncoated Tag	Polypropylene	Tyvek®
Coated Tag	Polyethylene	Tyvek Brillion®
Coated Face Sheets	Polystyrene	Valeron®
Uncoated Face Sheets	Polyolefin	
Gloss Sheets	Vinyl (Topcoat)	

RECOMMENDED APPLICATIONS

AUTOMOTIVE



COMPLIANCE



ELECTRONICS



FOOD & BEVERAGE



INVENTORY & LOGISTICS



OUTDOOR



PHARMACEUTICAL



RETAIL



The information on this datasheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

DNP Imagingcomm America Corporation

1001 Technology Drive | Mount Pleasant, PA 15666

Phone: 1.888.569.7222 | Fax: 1.800.676.7669

Email: info@dnp.imagingcomm.com | Web: am.dnpribbons.com



DNP