

R300 General Purpose Resin

RIBBON PROPERTIES

Ink Color	Black
Base Film Thickness	4.5 ± 0.4 μ
Ink Thickness	1.3 ± 0.4 μ
Total Thickness	5.8 ± 0.8 μ
Transfer Temperature	390°F / 199°C

PRODUCT FEATURES

- FDA Indirect Food Contact
- REACH Compliant
- RoHS Compliant
- BS5609

RECOMMENDED SUBSTRATES

SYNTHETICS	SPECIALTY MATERIALS
Polypropylene	Polyimide
Polyethylene	PVC Shrink Wrap
Polystyrene	
Vinyl (Topcoat)	
Polyesters (Gloss)	
Polyesters (Matte)	

RECOMMENDED APPLICATIONS

AUTOMOTIVE	CHEMICALS	COMPLIANCE	ELECTRONICS	FOOD & BEVERAGE
				
HEALTH & BEAUTY	INVENTORY & LOGISTICS	OUTDOOR	PHARMACEUTICAL	RETAIL
				

UL / cUL LABELING REFERENCES

3M:	PGJI2.MH16411, PGJI2.MH18072, PGJI2.MH45276
Avery Dennison:	PGJI8.MH17205, PGJI8.MH20558, PGJI8.MH20580, PGJI8.MH26285, PGJI8.MH27538
FLEXcon:	PGJI2.MH16635
Mactac:	PGJI2.MH26726
UPM Raflatac:	PGJI2.MH26760

The information on this datasheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

DNP Imagingcomm America Corporation

1001 Technology Drive | Mount Pleasant, PA 15666
 Phone: 1.888.569.7222 | Fax: 1.800.676.7669
 Email: info@dnp.imagingcomm.com | Web: am.dnpribbons.com



DNP