

✓200 Versatile Wax/Resin (formerly MP Mid)

RIBBON PROPERTIES

Ink Color	Black
Base Film Thickness	4.0 ± 0.3 μ
Ink Thickness	3.1 ± 0.2 μ
Total Thickness	7.1 ± 0.5 μ
Transfer Temperature	188°F / 87°C

RECOMMENDED SUBSTRATES

TAG / PAPER	SYNTHETICS	SPECIALTY MATERIALS
Uncoated Tag	Polypropylene	Tyvek®
Coated Tag	Polyethylene	Tyvek Brillion®
Coated Face Sheets	Polystyrene	Valeron®
Uncoated Face Sheets	Polyolefin	
Gloss Sheets	Vinyl (Topcoat)	

RECOMMENDED APPLICATIONS

AUTOMOTIVE



COMPLIANCE



ELECTRONICS



FOOD & BEVERAGE



HEALTH & BEAUTY



INVENTORY & LOGISTICS



OUTDOOR



PHARMACEUTICAL



RETAIL



UL / cUL LABELING REFERENCES

Avery Dennison: PGJI8.MH17205

FLEXcon: PGJI2.MH16635

PRODUCT FEATURES



VERSATILITY
SERIES



Sharp

Superior small character clarity



Durable

Abrasion and solvent resistant

PLUS:

- Reduced Print Energy
- FDA Indirect Food Contact
- Halogen-free
- REACH Compliant
- RoHS

The information on this datasheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

DNP Imagingcomm America Corporation

1001 Technology Drive | Mount Pleasant, PA 15666

Phone: 1.888.569.7222 | Fax: 1.800.676.7669

Email: info@dnpi.com | Web: am.dnpribbons.com



DNP