

✓300 Versatile Resin

RIBBON PROPERTIES

Ink Color	Black
Base Film Thickness	4.5 ± 0.4 μ
Ink Thickness	1.3 ± 0.4 μ
Total Thickness	5.8 ± 0.8 μ
Transfer Temperature	390°F / 199°C

RECOMMENDED SUBSTRATES

TAG / PAPER	SYNTHETICS	SPECIALTY MATERIALS
Coated Tag	Polypropylene	Polyimide
Gloss Sheets	Polyethylene	PVC Shrink Wrap
	Polystyrene	Tyvek®
	Polyolefin	Tyvek Brillion®
	Vinyl (Topcoat)	Valeron®
	Polyesters (Gloss)	
	Polyesters (Matte)	

RECOMMENDED APPLICATIONS

AUTOMOTIVE



COMPLIANCE



ELECTRONICS



FOOD & BEVERAGE



HEALTH & BEAUTY



INVENTORY & LOGISTICS



OUTDOOR



PHARMACEUTICAL



RETAIL



UL / cUL LABELING REFERENCES

3M:	PGJI2.MH16411
Avery Dennison:	PGJI8.MH17205
FLEXcon:	PGJI2.MH16635
Mactac:	PGJI2.MH26726

PRODUCT FEATURES



VERSATILITY
SERIES



Faster

50% faster than other resins



Durable

Abrasion and solvent resistant

PLUS:

- Reduced Print Energy
- FDA Indirect Food Contact
- REACH Compliant
- RoHS Compliant

The information on this datasheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

DNP Imagingcomm America Corporation

1001 Technology Drive | Mount Pleasant, PA 15666
Phone: 1.888.569.7222 | Fax: 1.800.676.7669
Email: info@dnp.imagingcomm.com | Web: am.dnpribbons.com



DNP